



1. A filter for liquids comprising one or more porous filters, wherein the one or more porous filters have pores of a nominal diameter between 0.1 and 10 microns and the one or more porous filters each have surfaces that are substantially neutral in a selected fluid.

A/B

RECEIVED
AUG 22 2001
TC 1700



2. The filter of any one of Claims 1 or 31 wherein the fluid is an aqueous fluid and the surface is substantially neutral over a preselected pH range.

RECEIVED
AUG 22 2001
TC 1700



AH

3. The filter of any one of Claims 1 or 31 wherein the one or more filters have a Zeta Potential of between about 10 and -10 millivolts in a selected fluid.


RECEIVED
AUG 22 2001
TC 1700



A1

4. The filter of any one of Claims 1 or 31 wherein the one or more filters have a Zeta Potential of between about 5 and -5 millivolts in a selected fluid.

RECEIVED
AUG 22 2001
TC 1700



5. A system for filtering fluids comprising a fluid and one or more porous filters wherein the one or more filters having pores of a nominal diameter between 0.1 and 10 microns and the one or more porous filters each having surfaces that are substantially neutral in a selected fluid.


A
B2

RECEIVED
AUG 22 2001
TC 1700



7. The filter of any one of Claims 1 or 31 wherein the one or
more filters have a log reduction value (LRV) of at least 3 of particles in the
selected fluid.

RECEIVED
AUG 22 2001
TC 1700



A2

8. The filter of any one of Claims 1 or 31 wherein the one or more filters have a log reduction value (LRV) of from about 3 to about 20 of particles in the selected fluid.

RECEIVED
AUG 22 2001
TC 1700



9. The filter of any one of Claims 1 or 31 wherein the one or more filters have a Zeta Potential of between about 10 and -10 millivolts in the selected fluid and a log reduction value (LRV) of at least 3 of particles in the selected fluid.

RECEIVED
AUG 22 2001
TC 1700



10. The filter of any one of Claims 1 or 31 wherein the one or more filters have a Zeta Potential of between about 5 and -5 millivolts in the selected fluid and a log reduction value (LRV) of at least 3 of particles in the selected fluid.

RECEIVED
AUG 22 2001
TC 1700



11. A method of filtration of liquids comprising selecting a fluid containing one or more contaminants to be removed, forming one or more porous filters, said one or more filters having pores of a nominal diameter between 0.1 and 10 microns and the one or more porous filters having surfaces which are substantially neutral within the selected fluid and passing the fluid through the one or more filters to remove the contaminants.

A2
B3

RECEIVED
AUG 22 2001
TC 1700



A2

12. The filter of any one of Claims 1 or 31 wherein the substantially neutral surface is inherent in the nature of the one or more filters.

RECEIVED
AUG 22 2001
TC 1700



A2 13. The filter of any one of Claims 1 or 31 wherein the substantially neutral surface is formed by surface modification of the one or more filters.

RECEIVED
AUG 22 2001
TC 1700



A2

14. The filter of any one of Claims 1 or 31 wherein the substantially neutral surface is formed by surface modification of the filter and the surface modification is selected from the group consisting of cross linking and grafting of one or more monomers on surfaces of the one or more filters.

RECEIVED
AUG 22 2001
TC 1700



A2 15. The filter of any one of Claims 1 or 31 wherein the substantially neutral surface is formed by surface modification of the filter and the surface modification is by application of an energy source on surfaces of the one or more filters.

RECEIVED
AUG 22 2001
TC 1700



A2 16. The filter of any one of Claims 1 or 31 wherein the one or more filters are made from a material selected from the group consisting of cellulose, glass, ceramics and metals.

RECEIVED
AUG 22 2001
TC 1700



12

17. The filter of any one of Claims 1 or 31 wherein the one or more filters are made from a material selected from the group consisting of cellulose, regenerated cellulose and nitrocellulose.

RECEIVED
AUG 22 2001
TC 1700



18. The filter of any one of Claims 1 or 31 wherein the one or more filters are made from a metal selected from the group consisting of stainless steel, nickel, chromium and alloys and blends thereof.

RECEIVED
AUG 22 2001
TC 1700



A7

19. The filter of any one of Claims 1 or 31 wherein the one or more filters are made from a plastic selected from the group consisting of polyolefins; copolymers or terpolymers of polyolefins; PVDF; PTFE resin; PFA; perfluorinated thermoplastic resins; PVC; nylons; polyamides; polyssulphones; polyethersulphones; polyarylsulphones; polyphenylsulphones; polyimides; polycarbonates; polyesters; and blends thereof.

RECEIVED
AUG 22 2001
TC 1700



42
B4

20. The filter of any one of Claims 1 or 31 wherein the one or more filters are made from a polyolefin selected from the group consisting of polyethylene, polypropylene and the like.

RECEIVED
AUG 22 2001
TC 1700



21. The filter of any one of Claims 1 or 31 wherein the one or more filters are made from an ultrahigh molecular weight polyethylene.

Az

RECEIVED
AUG 22 2001
TC 1700



22. A filter comprising one or more porous filters each having pores of a nominal diameter between 0.1 and 10 microns and the one or more porous filters having a surface having an IEP within a selected operating range of pH such that the filter surface either maintains a neutral or weak charge or does not acquire a highly charged surface within the selected pH range.

RECEIVED
AUG 22 2001
TC 1700



23. A filter comprising one or more porous filters each having pores of a nominal diameter between 0.1 and 10 microns and the one or more porous filters having a surface having an IPE that matches the pH of the liquid in which it is used.

A2

RECEIVED
AUG 22 2001
TC 1700



As

24. A filter of claim 23 comprising two or more filters in a composite filter, each with a different IEP.

RECEIVED
AUG 22 2001
TC 1700



25. The filter of any one of Claims 1 or 31 wherein the surface of the one or more filters is treated with one or more monomers selected from the group consisting of acrylate or acrylamide monomers and methacrylate or acrylamide monomers and blends thereof.

RECEIVED
AUG 22 2001
TC 1700



As

26. The filter of any one of Claims 1 or 31 wherein the surface of the one or more filters is treated with acrylic acid.

RECEIVED
AUG 22 2001
TC 1700



A2 27. The filter of any one of Claims 1 or 31 wherein the surface of the one or more filters is treated with acrylic acid, a photoinitiator and a cross linker.

RECEIVED
AUG 22 2001
TC 1700



A2 28. The filter of any one of Claims 1 or 31 wherein the surface of the one or more filters is treated with acrylic acid, a photoinitiator and a cross linker, wherein the cross linker is a N₁N¹methylenebisacrylamide.

RECEIVED
AUG 22 2001
TC 1700



A2 29. The filter of any one of Claims 1 or 31 wherein the surface of the one or more filters is treated with N_1N^1 methylenebisacrylamide.

RECEIVED
AUG 22 2001
TC 1700



30. The filter of any one of Claims 1 or 31 wherein the one or more filters have a log reduction value (LRV) of at least 3 of the particles of an average diameter that is smaller than the nominal pore size of the filter in the selected fluid.

RECEIVED
AUG 22 2001
TC 1700



Kelly
U.S. Serial No. 09/759,920
Preliminary amendment

Page

Please add the following claims.

31. The ~~filter~~ of Claim 1 wherein one or more pores filter have a nominal diameter between 0.1 and 1 microns.

REMARKS

Entry of this amendment is respectfully requested.

Respectfully submitted,

By Paul J. Cook

Paul J. Cook
Registration No. 20,820
Legal Department
Mykrolis Corporation
80 Ashby Road
Bedford, MA 01730-2271
Tel 781-533-600

RECEIVED
AUG 22 2001
TC 1700